

Flex-C-Ment™ Presents...

KEY COMPONENTS TO THE SYSTEM!



Primer 100:

- An extraordinary surface bonding agent that has exceptional qualities contributing to setting this overlay system apart from the rest
- Specifically designed for interior/exterior adverse and difficult applications



Modifier 300:

- Carefully blended polymer providing the integral part of the floor and wall overlay mixes
- Easy to use and time tested to give that flexural quality that earned its uniqueness



Overlay Mix:

- Cementitious dry mix designed for the most severe wear applications. Formulated to resist troweling air blisters and shrink cracks
- Balanced with additives to enhance curing in temperature extremes



Wall Mix-G:

- Sculpture performance cementitious dry mix designed specifically for deep wall textures creating that realistic appearance for various stone patterns
- Has been in testing and development for years to achieve optimum performance
- Lightweight insulated overlay material to apply directly over drywall, wood, masonry surfaces and other various surfaces without requiring a foundation
- Can be applied at a thickness of up to 2" without sagging



Wall Mix-W:

- Same qualities as Wall Mix-G, but also can be used for water proofing and/or in applications that require a light base color.



Underlay Mix:

- Super lightweight cementitious dry mix with highly insulative and flexural characteristics
- Used as an underlayment over wood and other unstable floor surfaces allowing for expansion and contraction
- Can be applied at thickness from 1/4" to over 2"
- May be used for floors or walls