



# OVERLAY MIX

## Product Name

Flex-C-Ment™ Overlay Mix  
Size: 55 lb bags

## Manufacturer

Yoder & Sons LLC  
1810-1 E Poinsett Street Ext.  
Greer, SC 29651  
(864) 877-3111  
Fax: (864) 877-2794  
[www.flex-c-ment.com](http://www.flex-c-ment.com)

## Description

This product is used for interior/exterior, driveways, patios, decks, floor and counter top surfaces. This high density, extra fine mix is created for long lasting protection from erosion and high traffic.

## Technical Data

Properties of Flex-C-Ment™ Overlay Mix when mixed with Flex-C-Ment™ Modifier

CURE TIME	COMPRESSIVE STRENGTH
7 days	2,800 psi
28 days	4,000 psi

## Installation

- Apply only to clean surfaces.
- MACHINE MIXING:
  - For each bag of Overlay Mix, add approx 1 ¼ gallons of mixed Flex-C-Ment™ Modifier
  - After adding mixed Flex-C-Ment™ Modifier, add Modifier until desired consistency is achieved
- HAND MIXING:
  - Empty bags into a suitable mixing container
  - For each bag of Overlay Mix, add approx 1 ¼ gallons of mixed Flex-C-Ment™ Modifier
  - Work the mix with a shovel, rake or hoe and add modifier as needed until desired consistency is achieved
  - Be sure all material is wet
  - Do not leave standing puddles



Flex-C-Ment™ Overlay Mix

## PRECAUTIONS

**IMPORTANT! READ BEFORE USING.**

This product contains portland cement. Contact with cement, freshly mixed concrete, or mortar can cause severe burns. Avoid direct contact with skin. Wash skin exposed to freshly mixed concrete or mortar directly or through soaked clothing promptly. If this product burns your skin, see a physician immediately.

If this product should contact eyes, immediately flush with water and consult a physician.

This product may contain silica. Silica dust if inhaled may cause respiratory or other health problems. Prolonged inhalation may cause delayed lung injury, including silicosis and possibly cancer.

Dust mask, eye protection and rubber boots and gloves are recommended when using this product.

- KEEP OUT OF THE REACH OF CHILDREN.

## Manufacturer's Warranty

The data, statements and recommendations herein are the results of tests we believe to be accurate and reliable, but do not constitute a warranty, expressed nor implied.

Installer assumes all liability for the use of this product and must use their own information and testing to evaluate its proper use for the desired result.

It shall be the sole responsibility of the manufacturer/seller to replace that portion of this product which proves defective during the three year period following its purchase, and neither shall be liable to buyer or to any third person for injury, direct or indirect loss, or damage related to this product.

Statements and recommendations are binding upon the manufacturer/seller only when in writing and properly signed by an officer of the manufacturer.